



AQT-MSV

MANUAL SOFTENER VALVE

AQT-MSV Manual Softener Valve

Aquatrol AQT-MSV Manual Softener Valves offer a simple to use manually controlled valve for easy operation. Used for water softening and other water treatment applications. The Aquatrol AQT-MSV Manual Softener Valves are available in 2.5" and 4" base and provide an easy to use lever for ease of operation.



AQT-MSV-1 Specifications:

Temp Range:	41 °F - 113 °F (5 °C - 45 °C)
Maximum Temperature:	122 °F (50 °C)
Pressure Range:	21.7 psi - 87 psi (1.49 bar - 5.99 bar)
Control Type:	Manual
Electricity:	None Required
Base:	2.5"
Inlet:	1"
Outlet:	1"
Drain:	1"
Riser Pipe:	1.05" OD
Brine Line:	3/8"
Water Capacity Service:	17.02 gpm @ 21.8 psi (64.43 lpm @ 1.50 bar)
Water Capacity Back Wash:	6.7 gpm @ 21.8 psi (25.36 lpm @ 1.50 bar)
Softener Tank Size:	6" - 16"

Material of Construction:

Body:	Noryl
Handle:	Metal
Internal Disc:	Ceramic



AQT-MSV-2 Specifications:

Temp Range:	41 °F - 113 °F (5 °C - 45 °C)
Maximum Temperature:	122 °F (50 °C)
Pressure Range:	21.7 psi - 87 psi (1.49 bar - 5.99 bar)
Control Type:	Manual
Electricity:	None Required
Base:	4"
Inlet:	2"
Outlet:	2"
Drain:	1.5"
Riser Pipe:	1.96" OD
Brine Line:	1/2"
Water Capacity Service:	36.4 gpm @ 21.8 psi (137.8 lpm @ 1.50bar)
Water Capacity Back Wash:	25.1 gpm @ 21.8 psi (95.01 lpm @ 1.50 bar)
Softener Tank Size:	14" - 30"

Material of Construction:

Body:	Noryl
Handle:	Plastic
Internal Disc:	Ceramic

LIT-AQT-MSV-SS 07/11/16



AQUATROL | P.O. Box 2235 Chino Hills, CA 91709 • USA

Distributed by:

WWW.AQUATROLTECH.COM