




AT SERIES

PRESSURE TANKS



Operating Parameters:

Maximum Operating Pressure: 150 psi (10.5 bar)

Maximum Operating Temperature: 120° F (49° C)

Waranty:

10 Year Warranty for: 6" - 13" vessels

5 Year Warranty for: 14" - 63" vessels

* For complete installation and handling instructions, please visit:
http://aquatroltech.com/dl/AQT_Tanks_Manual.pdf

DESIGN PARAMETERS

- Cycle Test
- Safety Factor

SAFETY FACTORS

- 100,000 Cycle Test without leaks
- Safety Factor
4:1 (Minimum burst at 600 psi)



Certified to
NSF/ANSI Standard 61 for
materials requirements only.

COMPONENT



AQUATROL | P.O. Box 2235 Chino Hills, CA 91709 • USA

Distributed by:

WWW.AQUATROLTECH.COM

	SIZE			CHARACTERISTICS		CAPACITY	
	Part Number	Inches	Millimeters	Connection	Color	Gallons	Liters
6"	AT-0618BL-25T	06x18	152x457	2.5" T	Blue	1.8	6.7
	AT-0713BL-25T	07x13	178x 330	2.5" T	Blue	1.9	7.2
7"	AT-0713BK-25T	07x13	178x 330	2.5" T	Black	1.9	7.2
	AT-0717BK-25T	07x17	178x 432	2.5" T	Black	2.5	9.5
	AT-0735BL-25T	07x35	178x889	2.5" T	Blue	5.2	19.7
8"	AT-0817BL-25T	08x17	203x432	2.5" T	Blue	2.9	11.0
	AT-0835BL-25T	08x35	203x889	2.5" T	Blue	6.6	24.8
	AT-0844BL-25T	08x44	203x1118	2.5" T	Blue	8.7	32.9
	AT-0844BK-25T	08x44	203x1118	2.5" T	Black	8.7	32.9
9"	AT-0935BL-25T	09x35	229x889	2.5" T	Blue	8.3	31.4
	AT-0948BL-25T	09x48	229x1219	2.5" T	Blue	12.7	48.1
	AT-0948BK-25T	09x48	229x1219	2.5" T	Black	12.7	48.1
10"	AT-1017BL-25T	10x17	254x432	2.5" T	Blue	4.4	16.8
	AT-1035BL-25T	10x35	254x889	2.5" T	Blue	10.2	38.6
	AT-1044BL-25T	10x44	254x1118	2.5" T	Blue	13.1	49.6
	AT-1054BK-25T	10x54	254x1372	2.5" T	Black	16.4	62.1
	AT-1054BL-25T	10x54	254x1372	2.5" T	Blue	16.4	62.1
12"	AT-1248BL-25T	12x48	305x1219	2.5" T	Blue	21.0	79.3
	AT-1252BL-25T	12x52	305x1321	2.5" T	Blue	22.2	84.0
	AT-1252BK-25T	12x52	305x1321	2.5" T	Black	22.2	84.0
	AT-1265BL-25T	12x65	305x1651	2.5" T	Blue	22.2	84.0
13"	AT-1354BL-25T	13x54	330x1372	2.5" T	Blue	27.5	104.1
	AT-1354BK-25T	13x54	330x1372	2.5" T	Black	27.5	104.1
14"	AT-1465BL-25T	14x65	356x1651	2.5" T	Blue	40.6	153.7
	AT-1465BK-25T	14x65	356x1651	2.5" T	Black	40.6	153.7
	AT-1465BL-4T	14x65	356x1651	4" T	Blue	40.6	153.7
16"	AT-1665BL-25T	16x65	406x1651	2.5" T	Blue	49.0	185.5
	AT-1665BK-25T	16x65	406x1651	2.5" T	Black	49.0	185.5
	AT-1665BL-4T	16x65	406x1651	4" T	Blue	49.0	185.5
	AT-1665NA-4T4B	16x65	406x1651	4" T 4" B	Natural	49.0	185.5
18"	AT-1865NA-4T	18x65	457x1651	4" T	Natural	66.7	252.5
	AT-1865NA-4T4B	18x65	457x1651	4" T 4" B	Natural	66.7	252.5
21"	AT-2162NA-4T	21x62	533x1575	4" T	Natural	88.0	333.1
	AT-2162NA-4T4B	21x62	533x1575	4" T 4" B	Natural	88.0	333.1
24"	AT-2472NA-4T	24x72	610x1829	4" T	Natural	126.8	480.0
	AT-2472NA-4T4B	24x72	610x1829	4" T 4" B	Natural	126.8	480.0
30"	AT-3072NA-4T	30x72	762x1829	4" T	Natural	195.5	740.0
	AT-3072NA-4T4B	30x72	762x1829	4" T 4" B	Natural	195.5	740.0
36"	AT-3672NA-4T	36x72	914x1829	4" T	Natural	283.0	1071.3
	AT-3672NA-4T4B	36x72	914x1829	4" T 4" B	Natural	283.0	1071.3
	AT-3672NA-6T6B	36x72	914x1829	6" T 6" B	Natural	271.3	1027.0
	AT-3694NA-6T6B	36x94	914x2388	6" T 6" B	Natural	271.3	1027.1
42"	AT-4272NA-6T6B	42x72	1066x1829	6" T 6" B	Natural	290.6	1100.0
48"	AT-4872NA-6T6B	48x72	1219x1829	6" T 6" B	Natural	477.7	1808.3
	AT-4894NA-6T6B	48x94	1219x2388	6" T 6" B	Natural	657.1	2487.0
	AT-6094NA-6T6B	60x94	1524x2388	6" T 6" B	Natural	710.2	2688.0
60"	AT-60110NA-6T6B	60x110	1524x2794	6" T 6" B	Natural	896.2	3392.0
	AT-6370NA-6T6B	63x70	1600x1778	6" T 6" B	Natural	687.0	2600.6
63"	AT-6383NA-6T6B	63x83	1600x2108	6" T 6" B	Natural	832.3	3150.0