



AQT-MFV-2

MANUAL FILTER VALVE



AQT-MFV-2 Manual Filter Valve

Aquatrol AQT-MFV-2 Manual Filter Valves offer a simple to use manually controlled valve for easy operation. Used with activated carbon filtration and other water treatment applications. The Aquatrol AQT-MFV-2 Manual Filter Valves are available in 4" base and provide an easy to use lever operation for moving from Service, to Rinse and to Back Wash positions.

AQT-MFV-2 Specifications:

Temp Range:	41 °F - 113 °F (5 °C - 45 °C)	Outlet:	2"
Pressure Range:	14 psi - 87 psi (0.96 bar - 5.99 bar)	Drain Line:	2"
Control Type:	Manual	Riser Pipe:	1.96" OD
Electricity:	None Required	Water Capacity Service:	44 gpm @ 21.8 psi (166.6 lpm @ 1.50 bar)
Mounting Base:	4" 8 UN	Water Capacity Back Wash:	44 gpm @ 21.8 psi (166.6 lpm @ 1.50 bar)
Inlet:	2"	Filters:	14" - 24"

Material of Construction:

Body:	Noryl
Handle:	Plastic
Internal Disc:	Ceramic

LIT-AQT-MFV-2-DS 06/17/20



AQUATROL | P.O. Box 2235 Chino Hills, CA 91709 • USA

Distributed by: