



AQT-MSV-2

MANUAL SOFTENER VALVE



AQT-MSV-2 Manual Softener Valve

Aquatrol AQT-MSV-2 Manual Softener Valves offer a simple to use manually controlled valve for easy operation. Used for water softening and other water treatment applications. The Aquatrol AQT-MSV-2 Manual Softener Valves are available in 4" base and provide an easy to use lever for ease of operation.

AQT-MSV-2 Specifications:

Temp Range:	41 °F - 113 °F (5 °C - 45 °C)	Drain Line:	1"
Pressure Range:	14 psi - 87 psi (0.96 bar - 5.99 bar)	Riser Pipe:	1.96" OD
Control Type:	Manual	Brine Line:	1/2"
Electricity:	None Required	Water Capacity Service:	44 gpm @ 21.8 psi (166.6 lpm @ 1.50bar)
Mounting Base:	4" 8 UN	Water Capacity Back Wash:	25.1 gpm @ 21.8 psi (95.01 lpm @ 1.50 bar)
Inlet:	2"	Softener:	14" - 30"
Outlet:	2"		

Material of Construction:

Body:	Noryl
Handle:	Plastic
Internal Disc:	Ceramic

LIT-AQT-MSV-2-DS 06/23/20



AQUATROL | P.O. Box 2235 Chino Hills, CA 91709 • USA

Distributed by: