



AQT-315

PRODUCT SPECIFICATIONS

AQT-315 Control Valves

Aquatrol 315 Control Valves are made of solid lead-free brass for strength and durability. The AQT-315 also offers a NH piston option and has a time-tested piston, seal and spacer design. The AQT-315 also offers a fully adjustable 5 cycle controller that allows you to control the upflow backwash, downflow brining and slow rinse, rapid rinse, timed brine refill and downflow service. The AQT-315 is ideal for filter applications.

FEATURES

- 2" Control valve
- Lead free brass body
- Adjustable 5 cycle control (Mech. & Digital NX)
- Backwash capacity accommodates tanks up to 42" (Filter) and 63" (Softeners) diameter
- Side Mount option
- NH option available
- Time clock: 12 days
- Meter NX: immediate / delayed regeneration
- Digital NX Controller:
 - Remote Signal
 - Aux. Relay
 - Chemical Pump Option
 - English / Spanish Language



Models:	
AQT-315ST-HW:	Softener Timer - HW
AQT-315ST-NH:	Softener Timer - NH
AQT-315SM-HW:	Softener Meter - HW
AQT-315SM-NH:	Softener Meter / NH
AQT-315S-NX-HW:	Digital Softener Timer / Meter - HW
AQT-315S-NX-NH:	Digital Softener Timer / Meter - NH
AQT-315FT:	Filter Timer
AQT-315F-NX:	Digital Filter Timer

HW - Hard Water Bypass. NH - No Hard Water Bypass.

Flow Rate 50 psi (3.5 bar) Valve Alone:	
Continuous 15 psi (1 bar) Drop:	95 gpm (360 lpm)
Peak 25 psi (1.7 bar) Drop:	124 gpm (470 lpm)
Max Backwash 25 psi (1.7 bar) Drop:	105 gpm (398 lpm)
CV 1 psi (0.07 bar) Drop:	24.8

Regeneration/Backwash:	
Downflow/Upflow:	Downflow or Upflow
Cycles:	5
Adjustable Cycles:	All
Time Available:	Mechanical 164 Min. / Digital NX 0-4 Hours Each Cycle

Meter NX:	
Accuracy:	3 - 150 gpm (11.5 - 568 lpm) ± 5%
Capacity Range:	0 - 999,999,999 gal

Valve Specifications:	
Inlet/Outlet:	2" NPT
Mounting Base:	4" - 8 UN
Distributor Pilot:	2.49" OD (2" SCH 40)
Drain Line:	2"
Brine Line:	1"
Height:	10" (254 mm)
Weight (Valve Gross):	Timer 41.9 lb (19 kg) Meter 48.5 lb (22 kg)

Additional Information:	
Electrical Rating:	24V - 50Hz, 60Hz
Max. VA	85 VA
Water Pressure:	Hydrostatic: 300 psi (20 bar) Working: 20 - 125 psi (1.4 - 8.6 bar)
Temperature:	34 - 110 °F (1 - 43 °C)

LIT-AQT-315-DS 05/04/22



AQUATROL | P.O. Box 2235 Chino Hills, CA 91709 • USA

Distributed by: