



AQT-910XT

PRODUCT SPECIFICATIONS

AQT-910XT Twin Alternating Digital Valve

Aquatrol AQT-910XT Twin series control valves offer a rigid valve body made from Noryl material for superior quality and durability. AQT-910XT with their diverse options and added security features allow for ease of use, while offering value added options to fit a wide range of applications. AQT-910XT valves are easy to maintain with multiple quick connect connectors, easy access to injectors and simplified programming. They can be used on softener tanks up to 16".



Features:

- Adjustable 6 cycles
- Historic Values
- Seals & Spacers new Stack Design
- Inlet/Outlet Quik Adaptors
- Accesible Injector Module
- Accesible Flow Meter
- QC (Quick Connect) Brine Connector
- Soft Water Refill
- Intelligent Proportional Regeneration
- DP Switch With Remote Signal
- New Bypass Design (Included)

Models:	
AQT-910SM-XT	Softener Twin 1.0" Valve, XT Controller
Flow Rate @50 psi, 3.5 bar (valve alone):	
Continuous 15 psi (1 bar) Drop:	18 gpm (68 lpm)
Peak 25 psi (1.7 bar) Drop:	24 gpm (91 lpm)
Max Backwash 25 psi (1.7 bar) Drop:	9 gpm (34 lpm)
CV 1 psi (0.07 bar) Drop:	4.8
Regeneration/Backwash:	
Downflow/Upflow:	Downflow
Cycles:	6, all adjustable
Time Available:	Up to 999 minutes per cycle
Meter:	
Accuracy Range:w	± 5%
Capacity Range:	0.3 - 26.5 gpm

Valve Specifications:	
Inlet/Outlet:	1.0"
Mounting Base:	2.5"
Distributor Pilot:	1.05" OD (3/4" SCH 40)
Drain Line:	1/2" Quick Connect, Elbow
Brine Line:	3/8" Quick Connect, Elbow
Height:	7" (180 mm)
Weight (Valve Gross):	8.8 lb (4 kg)

Additional Information:	
Electrical Rating Output:	Switching Transformer 100 - 240 V AC, 50/60 Hz, 0.4 A Max
Electrical Rating Input:	12.0 V DC, 1.0 A
Water Pressure:	Hydrostatic: 300 psi (21 bar) Working: 20 - 120 psi (1.4 - 8 bar)
Temperature:	34 - 110 °F (1 - 43 °C)
Softener Tanks:	7" - 16"

LIT-AQT-910XT-DS 05/09/22



AQUATROL | P.O. Box 2235 Chino Hills, CA 91709 • USA

Distributed by: