



# AQT-MSV-2

## MANUAL SOFTENER VALVE



### AQT-MSV-2 Manual Softener Valve

Aquatrol AQT-MSV-2 Manual Softener Valves offer a simple to use manually controlled valve for easy operation. Used for water softening and other water treatment applications. The Aquatrol AQT-MSV-2 Manual Softener Valves are available in 4" base and provide an easy to use lever for ease of operation.

### AQT-MSV-2 Specifications:

<b>Temp Range:</b>	41 °F - 113 °F (5 °C - 45 °C)	<b>Drain Line:</b>	1"
<b>Pressure Range:</b>	14 psi - 87 psi (0.96 bar - 5.99 bar)	<b>Riser Pipe:</b>	1.96" OD
<b>Control Type:</b>	Manual	<b>Brine Line:</b>	1/2"
<b>Electricity:</b>	None Required	<b>Water Capacity Service:</b>	44 gpm @ 21.8 psi (166.6 lpm @ 1.5 bar)
<b>Mounting Base:</b>	4" - 8 UN	<b>Water Capacity Back Wash:</b>	25.1 gpm @ 21.8 psi (95 lpm @ 1.5 bar)
<b>Inlet:</b>	2"	<b>Softener:</b>	14" - 24"
<b>Outlet:</b>	2"		

### Material of Construction:

<b>Body:</b>	Noryl
<b>Handle:</b>	Plastic
<b>Internal Disc:</b>	Ceramic

### Distributor:

<b>Top:</b>	AQT-TD-MV2
<b>Bottom:</b>	AQT-BD-1196-07 AQT-BD-1197-07

LIT-AQT-MSV-2-DS 08/14/20



AQUATROL | P.O. Box 2235 Chino Hills, CA 91709 • USA

Distributed by: