



AQT-MSV-34 & AQT-MSV-1

MANUAL SOFTENER VALVES

AQT-MSV-34 & AQT-MSV-1 Manual Softener Valves

Aquatrol AQT-MSV-34 & AQT-MSV-1 Manual Softener Valves offer a simple to use manually controlled valve for easy operation. Used for water softening and other water treatment applications. The Aquatrol AQT-MSV-34 & AQT-MSV-1 Manual Softener Valves are available in 2.5" base and provide an easy to use lever for ease of operation.



AQT-MSV-34 Specifications:

Temp Range:	41 °F - 113 °F (5 °C - 45 °C)
Pressure Range:	14 psi - 87 psi (0.96 bar - 5.99 bar)
Control Type:	Manual
Electricity:	None Required
Mounting Base:	2.5" - 8 NPSM
Inlet:	3/4"
Outlet:	3/4"
Drain Line:	1/2"
Riser Pipe:	1.05" OD
Brine Line:	3/8"
Water Capacity Service:	9 gpm @ 21.8 psi (34 lpm @ 1.5 bar)
Water Capacity Back Wash:	4 gpm @ 21.8 psi (15 lpm @ 1.5 bar)
Softener:	6" - 10"

Material of Construction:

Body:	Noryl
Handle:	Plastic
Internal Disc:	Ceramic

Distributor:

Top:	Included
Bottom:	Included



AQT-MSV-1 Specifications:

Temp Range:	41 °F - 113 °F (5 °C - 45 °C)
Pressure Range:	14 psi - 87 psi (0.96 bar - 5.99 bar)
Control Type:	Manual
Electricity:	None Required
Mounting Base:	2.5" - 8 NPSM
Inlet:	1"
Outlet:	1"
Drain Line:	1/2"
Riser Pipe:	1.05" OD
Brine Line:	3/8"
Water Capacity Service:	19 gpm @ 21.8 psi (71.9 lpm @ 1.5 bar)
Water Capacity Back Wash:	6.7 gpm @ 21.8 psi (25.3 lpm @ 1.5 bar)
Softener:	6" - 16"

Material of Construction:

Body:	Noryl
Handle:	Metal
Internal Disc:	Ceramic

Distributor:

Top:	Included
Bottom:	Included

LIT-AQT-MSV-34-MSV-1-DS 08/12/20



AQUATROL | P.O. Box 2235 Chino Hills, CA 91709 • USA

Distributed by: